



XR-Series

Our XR-Series trenching attachments are the most advanced ever made. They include significant advances in strength, durability, and efficiency over previous designs.

Features include a 50,000 lb. (22,680 kg) digging chain, removable double-flighted spoil auger, self-aligning boom with grease cylinder tensioning system, maintenance-free tapered roller bearings in the nose, longer life boom roller, and high operating pressure capability.

Choose the center trench position for most conditions and for maximum performance. For those times when you need to trench closer to a building or obstruction, use the manual side-shift or the optional hydraulic side shift.







Model	Base Machine Recommended Flow	Trench Depth	Trench Width
XR-7	8-15 GPM - 1,700-3,000 PSI	2'-3' (.61m91m)	4"-8" (102mm-
XR-14	10-20 GPM - 1,900-3,000 PSI	2'-4' (.61m-1.22m)	6"-12" (152mm-
XR-21	13-25 GPM - 2,000-3,000 PSI	2'-5' (.61m-1.52m)	6"-12" (152mm-
XRHP-21	13-25 GPM - 2,000-3,500 PSI	2'-5' (.61m-1.52m)	6"-12" (152mm-
XR-25	16-25 GPM - 2,000-3,000 PSI	2'-5' (.61m-1.52m)	6"-12" (152mm-
XRHP-25	16-25 GPM - 2,000-3,500 PSI	2'-5' (.61m-1.52m)	6"-12" (152mm-
XR-35	20-40+ GPM - 2,000-4,200 PSI	2'-5' (.61m-1.52m)	6"-12" (152mm-

XR-Series Enhancements

- Stronger, self-aligning boom design with improved grease cylinder tensioning system.
- Stronger, more wear-resistant drive shaft.
- Stronger, maintenance-free tapered roller bearings in boom nose.
- Easier field maintenance of service and parts.
- New, more wear-resistant end-boom roller reduces bearing load, increases digging chain life, and virtually eliminates lockup.
- Redesigned trencher housing improves visibility, trench starting, and digging capability.
- Optional trench cleaner improves trench cleanout and is even more durable than previous models.
- *NEW, EVEN STRONGER, LOWE*-HYDRAULIC MOTORS WITH HIGH PRESSURE RATINGS*

www.romeco.com.ar 2