

## REGLAS HÚMEDAS Wacker Neuson **P35A**



### Vibratory screeds

When finishing concrete floors Wacker Neuson's wet screed carries out three working processes in one: spreading, screeding and compacting. Not only is this extremely practical, the device is also very easy to use. The carrying handles make it easy to move the P35A over the concrete and delivers first-class results in the process. It is suitable for all kinds of concrete, because the centrifugal force is adjustable to 7 positions.

- Extremely mobile device concept
- Easy to operate:
- Encapsulated eccentric casing to protect from dirt, concrete and splash water

## P35A Technical specifications

### Wet screed P35A

Weight	15.5 kg
Engine / Motor	Air-cooled single-cylinder four-cycle gasoline engine
Engine / Motor manufacturer	Honda
Displacement	35.8 cm <sup>3</sup>
Engine performance	1.0 (1.3) kW (hp)
at rpm	7,000 rpm
Tank capacity	0.65 l
Fuel consumption	0.6 l/h
Length	1,117 mm
Width	889 mm

### 1.200–2.400 mm profile lengths

	SBW4F	SBW15M	SBW6F	SBW20M	SBW8F
Weight kg	3.8	4.6	5.4	6.1	7.6
Length mm	1,200	1,500	1,800	2,000	2,400
Width mm	165	165	165	165	165

### 3.000 - 4.900 mm profile lengths

	SBW10F	SBW12F	SBW14F	SBW16F
Weight kg	9.5	11.4	13.3	15.2
Length mm	3,000	3,700	4,300	4,900
Width mm	165	165	165	165