

ROMECO

SOLUCIONES PARA TUS PROYECTOS



PAVIMENTADORA DE RODILLO

Allen TRTP75



The lightest weight and least expensive machine in the TRTP product group, the 75 enables contractors to use a machine that handles small paving pours that would otherwise be too heavy for a truss screed. This unit is a nice addition to the Triple Tube Paver Group with some of the features and functions of the larger size machines.

SPECIFICATIONS

DESCRIPTION	TRTP75
ENGINE	Honda EFI
HORSEPOWER CLASS	22 hp (27.6 kW)
FUEL TYPE	Gasoline
WIDTHS AVAILABLE (2 FT INCREMENTS)	14 - 22 ft (3.6 - 9.7 m)
WEIGHT AT 22 FT	2,626 lbs (1,191 kg)
ROLLER TUBE DIAMETER	6" or 8"
TUBE WEIGHT PER FT	19 lbs (9 kg) / 21 lbs (9.5 kg)
HYDRAULIC OIL RESERVOIR	9 gal (34 L)
HYDRAULIC SPRAY SYSTEM	OPTION
HYDRAULIC STEERING LEG	OPTION

STEEL EDGE FORMS AND ACCESSORIES


Allen offers a complete line of steel edge forms, including straight forms, radius, dual-sided and heavy-duty paving forms (dowel holes upon request).



ALL MODELS

HYDRAULIC STEERING LEG


Hydraulic steering leg allows the operator the ability to straighten the machine while paving and "steer" through a radius pour.



ALL MODELS

SPRAY SYSTEM

Allows fogging of screeding tube to keep concrete from sticking to the tube. Fog bar is made with QD couplings for ease of assembly for machine reconfiguration. Available on all models.



ALL MODELS

TUBE SCRAPERS

Drive tube scrapers prevent build-up on tubes allowing for easier clean-up at the end of the day. Available on all models.